



## **Protective Gloves Oilatex**

Size:	S/7	M / 8	L/9	XL / 10	XXL / 11
Ref:	11 645	11 646	11 647	11 648	11 649

Packing: 12 pairs per polybag 120 pairs per carton

User Manual / User Instructions

Standards applied:

EN 420:2003+A1:2009, EN 388:2016, Regulation (EU) 2016/425



Material:

Textile: elastane, nylon Coating: nitrile microfoam coating

## **EU Type-Examination**

## Protection against mechanical risks EN 388

EN 388:2016 Test criteria Abrasion re

4141X

Test criteria Performance level 0 1 2 3 4 Abrasion resistance (Cycles) (0-4)0 1 2 3 4 5 Blade cut resistance - Coupe-Test (Index) (0-5)0 1 2 3 4 (0-4)Tear resistance (Newton) 0 1 2 3 4 (0-4)Puncture resistance (Newton) ABCDEF Cut resistance by sharp objects EN ISO 13997 (Newton) (A-F)


0 = lowest performance level; 5 = highest performance level


X = the glove has not been constructed for the application in this test

In the event of blunting during a cut resistance test, the results of the Coupe Test are to only be considered indicatory, whereas the TDM cut resistance test supplies reference results with regard to performance. The lab tests are intended to provide a selection guide, but they can not simulate actual workplace conditions. It is therefore the responsibility of the user and not of the manufacturer to check the suitability of a specific protective glove for the intended application. The equipment protects against medium mechanical risks.

## **User and Care Instructions**







**Transport:** Only transport gloves in their original packing.

Use: Before using gloves wash and dry hands carefully. One pair of working gloves should not be worn continuously for more than two hours. If gloves are worn continuously for long periods, it is recommended to change between several pairs. Observe performance levels of the gloves. Do not use the glove in vicinity of any rotating component where there is a risk of glove being trapped and pulled into the machine. Not suitable for use with electrical components. Wash hands thoroughly after wearing gloves and apply a suitable hand creme. Gloves should be dry before wearing them again. Specified protection levels are only provided on coated/reinforced areas. After contamination deterioration of glove material performance is possible. Employer and user must decide whether the gloves protect against the hazards which may occur at the respective work situation.

**Durability:** The durability depends on the degree of deterioration and the intensity of use in the respective area of application, but a maximum of two years. A precise information of time is therefore not possible.

Cleaning: Depending on the degree of soiling, shake off the dirt or dust or brush the glove with a soft brush after each use. Do not rub. Allow to air dry. The protective levels provided in the product descriptions refers exclusively to new, unused gloves. A transfer of the results to gloves after care treatment is not possible. Washing may reduce performance, check gloves carefully for damage before

**Disposal:** Correct handling requires the gloves to be disposed of in the household waste. Contaminated protective gloves which may pose a risk are to be disposed of professionally. Information can be obtained from the relevant waste disposal authorities.

Caution: Producer is not aware of any substances that can cause allergies when using the glove. This product is not a chemical protection glove. You can obtain the declaration of conformity through: www.sanger.de

Notified Body No.:

C€ 0321

EU Type-Examination and Surveillance by: SATRA Technology Centre Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

Sänger GmbH • Industriegebiet Herdwiesen • Zeller Weg 30 • 74575 Schrozberg / Germany • www.sanger.de